

T7 Plus Terminal

Integrated terminal with high-performance printer

Get the next generation T7 POS terminal:

- Eliminates paper jams with revolutionary SureLoad printer
- Prints receipts in half the time of previous generation printers
- Supports longer paper rolls for few paper changes
- Operates quietly and quickly



The Hypercom© T7 *Plus* builds on the heritage of Hypercom's popular T7 family of terminals selling more than 3 million units. This latest model is designed for merchants requiring a compact countertop POS terminal accepting all magnetic stripe cards and delivering fast online transaction authorizations.

The T7 *Plus* features the completely new SureLoad™ printer with significantly faster receipts delivery. It allows paper rolls to simply be dropped in place without feeding through slots and rollers and supports longer paper rolls at the request of the merchant community. The T7 *Plus* uses thermal paper and silently prints, its quiet operation is welcomed by both merchants and customers. An external PIN pad can be attached where required.

The 35-key keyboard allows one-step initiation of all daily functions and transactions types. The T7 *Plus* delivers a powerful feature set in an attractive, compact design. It offers low overall cost of operation thanks to its high reliability, communications capabilities, easy operation and advanced remote software management. The T7 *Plus* is a safe choice for merchants wanting a new credit/ debit card POS terminal.

For more information about the T7Plus, please call your TRI Sales Representative at 888-494-9004 or visit our website at www.transactionresources.com

T7Plus Specifications

Integrated terminal with high-performance printer

Display	Type	LCD
	Size	2 lines x 20 characters text display standard 4 lines x 20 characters text display optional
	Backlight	50,000 hours (calculated)
Card reader	Magnetic Stripe	Tracks 1, 2; Tracks 1, 2, 3, optional
	Reliability	400,000 reads (calculated)
Card option	IC interface	ISO 7816, EMV-compliant, non-captive
	SIMMLOCK	4 SAMs
Keypad	Elastomeric	35 keys, water-resistant; 3 soft keys optional
Comms	Modem	1200, 300 bps, V22, V21 synchronous (SDLC) & asynchronous; 2400 bps, RS232 with power or RS485 2-wire drop LAN an RS 232 without power
	Peripheral port	Compatible with P1300
Printer	SureLoad™	Clamshell design with drop-in paper loading, thermal technology, 384 dots per line
	Paper roll	57 mm wide; 80 mm diameter
Memory	RAM	1 MB; 512 KB (optional)
	RAM backup	5-year battery
	EPROM	32 KB
Power	AC	85-250 V, 50/60 Hz
	DC	24 V DC, 1A
Security	Physical	Intrusion detector
	Key mgmt (optional)	Master/ session keys (12) or DUKPT
Environment	Temperature	0-45 C/ 32-115 F
	Humidity	Max 85%, non-condensing
	ESD	12,000 volts
Footprint	Dimensions	10 in x 5.18 in x 2.5 in/25.4 cm x 13.2 cm x 6.35 cm
Weight		1.5 lbs/ 0.68 kg approximate weight
Product lifecycle	Reliability	80,000 hours (calculated), not including printer

Specifications subject to change without notice